

Microwave Farm's Compact N-Type Calibration Kits offers excellent performance characteristics that is specially designed for the fine-tuning in production environments and quality testing facilities using 50 ohm N-type connectors from **DC to 6, 8 GHz**.

This Cal. Kit include all needed calibration standard (Open, Short, Load) in one unit. It is best solution for available for ease of use in VNA calibration, especially in the field.



■ Features

- DC to 6, 8 GHz
- Standard kit included N-type (Male) OPEN-SHORT-LOAD

■ Application

- VNA, Full 2-port CAL.
- Test & Measurement
- Precision Calibration

■ Specification

Scope	Items	MFWWNT(M)	MFWWNT(M)-8G
Electrical	Freq. range	DC to 6 GHz	DC to 8 GHz
	Impedance	50 Ohm	
	Return loss (LOAD)	< -38 dB (DC to 6 GHz) <-37 dB (6 to 8 GHz)	< -42 dB (DC to 6 GHz)
	Phase deviation (OPEN,SHORT)		< 1.5 degrees
Mechanical	Connector type	N-Type (Male)	
	Housing		Stainless steel
	Weight		177 g

■ Calibration Coefficient

Type	Cal. Coefficient
OPEN	C0 $89.939 \times 10^{-15} \text{F}$
	C1 $2536.80 \times 10^{-27} \text{F/Hz}$
	C2 $-264.990 \times 10^{-36} \text{F/Hz}^2$
	C3 $13.4 \times 10^{-45} \text{F/Hz}^3$
	Offset delay 40.856 ps
	Offset Loss 0.93 GΩ/s
SHORT	L0 $3.3998 \times 10^{-12} \text{H}$
	L1 $-496.4808 \times 10^{-24} \text{H/Hz}$
	L2 $34.8314 \times 10^{-33} \text{H/Hz}^2$
	L3 $-0.7847 \times 10^{-42} \text{H/Hz}^3$
	Offset delay 45.955 ps
	Offset Loss 1.087 GΩ/s

■ Drawing

Unit : mm

